



# Devco Australia Holdings Pty Ltd

P O Box 14, Pinkenba Qld 4008

Ph +61 7 3260 2361

ABN 45 098 077 662

Fx +61 7 3260 2431

[www.sulphur.com.au](http://www.sulphur.com.au)

## PRILLED SULPHUR

### Product Specification

Product Code: PS

TEST	UNIT	LIMIT
Colour		Bright Yellow
Shape		Generally spherical
Size		~ 3 mm – 6 mm
Purity of Sulphur	% mass	99.8 % minimum
Carbon	% mass	0.1 % maximum
Ash	% mass	0.1 % maximum
Acidity ( H <sub>2</sub> SO <sub>4</sub> )	% mass	0.02 % maximum
H <sub>2</sub> S	% mass	20 ppm maximum
Moisture	% mass	5 % maximum
Arsenic	ppm mass	20 ppm maximum
Cadmium	ppm mass	5 ppm maximum
Copper	ppm mass	20 ppm maximum
Chloride	ppm mass	20 ppm maximum
Fluoride	ppm mass	20 ppm maximum
Lead	ppm mass	1.0 ppm maximum
Mercury	ppm mass	1.0 ppm maximum
Selenium	ppm mass	0.1 ppm maximum

#### Notes

1. Testing frequency and reporting requirements to be agreed with customer.
2. Refer to the Material Safety Data Sheet for safe handling information.

Author:	Allen Bromley	Issued:	22 July 2009
Approved by:	Allen Bromley	Supercedes:	21 April 2009
Doc. Name:	Product Specification Prilled Sulphur		