



Devco Australia Holdings Pty Ltd

P O Box 14, Pinkenba Qld 4008 ♦ Ph +61 7 3260 2361, Fx +61 7 3260 2431
ABN 45 098 077 662

www.sulphur.com.au

SUPER FINE PRILLED SULPHUR Product Specification

Product Code: SFPS

TEST	UNIT	LIMIT
Colour		Bright Yellow
Shape		Generally spherical
Size		~ 50 micron – 1 mm
Purity of Sulphur	% mass	99.8 % minimum
Carbon	% mass	0.1 % maximum
Ash	% mass	0.1 % minimum
Acidity (H ₂ SO ₄)	% mass	0.15 % maximum
H ₂ S	% mass	20 ppm maximum
Moisture	% mass	5 % maximum
Arsenic	ppm mass	20 ppm maximum
Cadmium	ppm mass	5 ppm maximum
Copper	ppm mass	20 ppm maximum
Chloride	ppm mass	20 ppm maximum
Fluorine	ppm mass	20 ppm maximum
Lead	ppm mass	2.0 ppm maximum
Mercury	ppm mass	1.0 ppm maximum
Selenium	ppm mass	5.0 ppm maximum

Notes

1. Testing frequency and reporting requirements to be agreed with customer.
2. Refer to the Material Safety Data Sheet for safe handling information.

Author:	Richard Aston	Issued:	15 May 2013
Approved by:	Richard Aston	Supersedes:	22 July 2009
Doc. Name:	Product Specification Super Fine Prilled Sulphur		