



Devco Australia Holdings Pty Ltd

P O Box 14, Pinkenba Qld 4008 ♦ Ph +61 7 3260 2361

ABN 45 098 077 662

www.sulphur.com.au

PRILLED SULPHUR Product Specification

Product Code: PS

| TEST | UNIT | TYPICAL ANALYSIS |
|--|----------|---------------------|
| Colour | | Bright Yellow |
| Shape | | Generally spherical |
| Size | | ~ 3 mm – 6 mm |
| Purity of Sulphur | % mass | 99.8 % minimum |
| Carbon | % mass | 0.1 % maximum |
| Ash | % mass | 0.1 % maximum |
| Acidity (H ₂ SO ₄) | % mass | 0.02 % maximum |
| H ₂ S | % mass | 20 ppm maximum |
| Moisture | % mass | 5 % maximum |
| Arsenic | ppm mass | 2 ppm maximum |
| Cadmium | ppm mass | 2 ppm maximum |
| Copper | ppm mass | 20 ppm maximum |
| Chloride | ppm mass | 20 ppm maximum |
| Fluorine | ppm mass | 150 ppm maximum |
| Lead | ppm mass | 10 ppm maximum |
| Mercury | ppm mass | 0.1 ppm maximum |
| Selenium | ppm mass | 0.1 ppm maximum |

Notes

1. Testing frequency and reporting requirements to be agreed with customer.
2. Refer to the Material Safety Data Sheet for the safe handling information.

| | | | |
|--------------|---------------------------------------|-------------|----------------|
| Author: | Guil Araldi | Issued: | 28 August 2024 |
| Approved by: | Richard Aston | Supersedes: | 05 August 2021 |
| Doc. Name: | Product Specification Prilled Sulphur | | |